

ALUMINUM X-SERIES HOOD.

GOOSENECK DIAMETER: .312

BULB SPECIFICATIONS:

12 VOLTS AC/DC

BAGS MINI-BAYONET BASE  
(SOCKET IS ISOLATED)



XLR CONNECTOR  
AVAILABLE 3 OR 4  
PIN CONFIGURATIONS

Standard 3-pin  
X and XR series wiring

Pin 1 - Jumpered to Ground Lug  
Pin 2 - Lamp Center Contact (Black)  
Pin 3 - Lamp Shell (White)

Standard 4-pin  
X and XR series wiring

Pin 1 - Not Connected  
Pin 2 - Not Connected  
Pin 3 - Lamp Shell (White)  
Pin 4 - Lamp Center Contact (Black)



### BULB OPTIONS

Q5	1815
5 WATTS 420mA	2.4 WATTS 230mA
HALOGEN	INCANDESCENT
HARD GLASS ENVELOPE	HARD GLASS ENVELOPE

Littlite LLC, 10087 Industrial Dr Hanburg MI, 48139,  
Phone, (810) 231-9373 Fax, (810) 231-1631  
[www.littlite.com](http://www.littlite.com)

All designs, construction and other disclosures set forth herein are the property of Littlite LLC. and such information is imparted to you in confidence. In accepting this information you agree not to reproduce it, to manufacture it, disclose it, or have it manufactured in whole or in part without written permission of Littlite LLC.

**Littlite®**

XR-SERIES  
OVERALL DIMENSIONS  
FILE # XR-SPEC Rev B